


Verso R 1000 FSA C5

Nominal air flow according to ErP 2018, m ³ /h	1000
Nominal air flow according to ErP 2018, l/s	278
Electric air heater capacity, kW / Δt, °C	3/8,8
Supply voltage HE, V	3~400
Maximal operating current HE, A	7,8
Power supply cable E, mm ²	5×1,5
Electric power input of the fan drive at maximum flow rate, W	123
Noise power level, L _{WA} , dB(A)	42
Noise pressure level, L _{PA} , dB(A), (3 m)	31
Filters dimensions B×H×L, mm	472×402×96
Unit dimensions B×H×L, mm	1050×485×3000
Panel thickness, mm	50
Maintenance space, mm	660
Unit weight, kg	238



Performance



Accessories

Closing damper	AGUJ-M-315+LM24
Outdoor grill	LD-315

Mounting positions





Temperature efficiency

Outside temperature, °C	Winter					Summer		
	-23	-15	-10	-5	0	25	30	35
After heat exchanger, °C	11,8	13,6	14,7	15,9	17,0	22,7	23,8	25,0

Indoor +22 °C, 20 % RH

Shown as right (R1)



▶ ODA – outdoor intake ▶ SUP – supply air ▶ ETA – extract indoor ▶ EHA – exhaust air